

Marine Fuses

- Fast-acting, corrosion resistant fuses open quickly to protect circuits from overloads and short-circuits.
- Time-delayed to allow temporary, harmless in-rush currents to pass but open on sustained overloads and short-circuits.



ATO®/ATC® Fuses

Diameter: 3/4" (19 mm)

Length: 3/4" (19 mm)

Maximum voltage: 32V DC

Rating (A)	Qty/Pkg	OEM #
1	1	J01A
2	1	J02A
3	1	J03A
5	1	J05A
7.5	1	J7.5A
10	1	J10A
15	1	J15A
20	1	J20A
25	1	J25A
30	1	J30A
40	1	J40A



MAXI® Fuses

Fuses available: 30-80A

Interrupt capacity: 1000A DC


Maximum voltage: 32V DC

Rating (A)	Qty/Pkg	Part #	OEM #
30	1	BFHD-30A/DSP	BFHD-30A
40	1	BFHD-40A/DSP	BFHD-40A
50	1	BFHD-50A/DSP	BFHD-50A
60	1	BFHD-60A/DSP	BFHD-60A
70	1	BFHD-70A/DSP	BFHD-70A
80	1	BFHD-80A/DSP	BFHD-80A



ANL Fuses

Use with:

- Pro Installer ANL Fuse Holders (page 35) 
- Tin plated
- Visible fuse status window
- 48V DC voltage rating
- Up to 3000A interrupt capacity

Length: 3.23" (82 mm)

Width: 0.88" (22 mm)


Stud clearance: 0.43" (11 mm)

Rating (A)	Qty/Pkg	Part #	OEM #
20	1	—	77049020
40	1	—	IP40
50	1	IP50P/DSP	IP50
63	1	IP63P/DSP	IP63
80	1	IP80P/DSP	IP80
100	1	IP100P/DSP	IP100
125	1	—	IP125
150	1	IP150P/DSP	IP150
160	1	—	77049160
175	1	—	IP175
200	1	IP200P/DSP	IP200
250	1	IP250P/DSP	IP250
300	1	IP300P/DSP	IP300
355	1	—	IP355
400	1	—	77049400
425	1	IP425P/DSP	IP425
500	1	IP500P/DSP	IP500



Heavy-duty ANL Fuses

Use with:

- 5/16" (8 mm) mounting studs
- Pro Installer ANL Fuse Holders (page 35) 

Rating (A)	Qty/Pkg	OEM #
600	5	FANL-600-B
675	5	FANL-675-B
750	5	FANL-750-B



Class T Fuses


Interrupt capacity: 20,000A DC

Maximum voltage: 160V DC

Diameter: 1.34" (34 mm)

Length: 2.77" (70 mm)

Use with:

- Pro Installer Class T Fuse Holders (page 35) 

Rating (A)	Qty/Pkg	OEM #
225	1	FT-225-B
250	1	FT-250-B
300	1	FT-300-B
350	1	FT-350-B
400	1	FT-400-B

Heavy-duty Class T Fuses


Interrupt capacity: 20,000A DC

Maximum voltage: 160V DC

Diameter: 1.62" (41 mm)

Length: 3.03" (77 mm)

Use with:

- Pro Installer Class T Fuse Holders (page 35) 

Rating (A)	Qty/Pkg	OEM #
450	1	FT-450-B
500	1	FT-500-B
600	1	FT-600-B