

# All-Round Plug-In Lights

## LIGHTARMOR™ LED Fast Action All-Round Navigation Lights

Premium LED lights with a flexible, impact-resistant composite pole make these perfect for anglers and hunters to maneuver through low-hanging obstacles. The subtle, glare-free black matte finish complements many of today's boat designs.

- ISO 19009:2015 Certified
- Meets standards ABYC C-5 & A-16, USCG CFR 183.810
- Impact-resistant polycarbonate lens
- Water resistant
- Corrosion/UV resistant
- Light head adjusts 15° fore to 15° aft
- LED light engines last for 50,000 hours
- 5-year warranty



Threaded Locking Collar fits securely with LightArmor Plug-In Light Bases

5530



| Description     | Pole Length | OEM Part # | Part #     |
|-----------------|-------------|------------|------------|
| All-Round Light | 24"         | 5530-24BP1 | 5530-24BP7 |
|                 | 30"         | 5530-30BP1 | —          |
|                 | 36"         | 5530-36BP1 | 5530-36BP7 |
|                 | 42"         | 5530-42BP1 | 5530-42BP7 |
|                 | 48"         | 5530-48BP1 | —          |
|                 | 54"         | 5530-54BP1 | 5530-54BP7 |
|                 | 60"         | 5530-60BP1 | —          |

## LIGHTARMOR™ LED All-Round Articulating Light

USCG certified. Provides 2-mile 360° visibility for boats up to 39.4 ft (12m)

- LightArmor™ All-Round navigation engine
- 30% lighter than earlier Attwood all-round lights
- Exclusive condensation management increases visibility
- Exclusive anti-glare engine preserves night vision
- Shock-, corrosion-, and water-proof electronics
- Durable, anodized aluminum pole
- Articulating head for use in all applications
- Strong locking-collar secures light in harsh marine conditions
- Standard 2-pin
- Compatible with Attwood and popular bases
- Operating range = 10.5V DC - 14.4V DC
- Over 50,000 hour life
- 5-year warranty



5530



OEM Threaded Locking Collar

Aftermarket Dual Locking Collar



| Series | Use with Light Base                          |
|--------|--|
| 5530   | 910R2, 910V2, 910T2, 2520‡, 911339‡, 911370‡ |

  

| Description               | Pole Length | OEM Part # | Part #    |
|---------------------------|-------------|------------|-----------|
| 2-Pin Locking-Collar Pole | 12"         | 5530-12T1  | —         |
|                           | 24"         | —          | 5530-24A7 |
|                           | 36"         | —          | 5530-36A7 |
|                           | 42"         | 5530-42T1  | 5530-42A7 |
|                           | 48"         | 5530-48T1  | 5530-48A7 |
|                           | 54"         | 5530-54T1  | 5530-54A7 |
|                           | 54", Black  | 5530-54TB1 | —         |
|                           | 60"         | 5530-60T1  | 5530-60A7 |
|                           | 66"         | 5530-66T1  | —         |

‡When locking collar is removed.