

Pro Installer Insulated Studs

Pro Installer Insulated studs are available in single and twin stud versions, featuring 8 mm (5/16") and 10 mm (3/8") variants. A double stud version with 10 mm and 8 mm studs is also included for extending outboard motor cables. The Power Tapping Plate single stud models provide convenient termination points for additional small cables. Pro Installer family features are replicated with these insulated studs, generous stud length, modular footprint, insulating covers with label recess, and common interconnection height.

Specifications:

- Power tapping plate: 4x 4 mm (5/16") terminals
- Maximum current through power tapping plate: 50A per terminal (4x 50A maximum)
- Note: no power passes through the stud so no amp rating is given 50V DC
- High temperature, fiber reinforced plastic base provides strength and chemical resistance
- Clear polycarbonate cover with snap-out extra cable access
- Stainless steel studs, screws and nuts for longevity in the marine environment
- Insert moulded studs with metric threads
- Double studs feature 'snap out' insulating partition, to allow linking of studs

Description	Part #	OEM #	Footprint*
Single 8 mm	IST-8MM-1S	IST-8MM-1S-B	0.5 x
Double 8 mm	IST-8MM-2S	IST-8MM-2S-B	0.5 x
Double 10 mm / 8 mm	IST-10MM-8MM	IST-10MM-8MM-B	0.5 x
Single 10 mm	IST-10MM-1S	IST-10MM-1S-B	0.5 x
Double 10 mm	IST-10MM-2S	IST-10MM-2S-B	0.5 x
Single 8 mm with power Tapping Plate	IST-8MM-1SPT	IST-8MM-1SPT-B	0.5 x
Single 10 mm with power Tapping Plate	IST-10MM-1SPT	IST-10MM-1SPT-B	0.5 x

* See page 33 for Footprint details

Related Products



Pro Installer
Link Bars
page 37



IST-8MM-1S



IST-8MM-2S



IST-10MM-8MM



IST-10MM-1S



IST-10MM-2S



IST-8MM-1SPT



IST-10MM-1SPT