

Model No.	Rated Volts DC	Fuse Size	Outlet Type	Check Valve	OEM Part #	OEM Outlet Straight	OEM Outlet 90°	Part #
T500	12V	3A	3/4" (19mm) & 1" (25mm) Barbs	Y	—	—	—	5606-7
	12V	3A	3/4" (19mm) Barb	N	5606B-1	—	—	—
	12V	3A	1-3/8" Threaded*	Optional	5606-1	AS5605S-1	AS5605E-1	—
T800	12V	5A	3/4" (19mm) & 1" (25mm) Barbs	Y	—	—	—	5608-7
	12V	5A	3/4" (19mm) Barb	N	5608B-1	—	—	—
	12V	5A	1-3/8" Threaded*	Optional	5608-1	AS5605S-1	AS5605E-1	—
T800	24V	2A	3/4" (19mm) & 1" (25mm) Barbs	Y	—	—	—	5609-7
	24V	2A	3/4" (19mm) Barb	N	5609B-1	—	—	—
	24V	2A	1-3/8" Threaded*	Optional	5609-1	AS5605S-1	AS5605E-1	—
T1200	12V	6A	1" (25mm) & 1-1/8" (28mm) Barbs	Y	—	—	—	5612-7
	12V	6A	1-1/8" (28mm) Barb	N	5612B-1	—	—	—
	12V	6A	1-3/8" Threaded*	Optional	5612-1	AS5612S-1	AS5612E-1	—
T1200	24V	3A	1" (25mm) & 1-1/8" (28mm) Barbs	Y	—	—	—	5613-7
	24V	3A	1-1/8" (28mm) Barb	N	5613B-1	—	—	—
	24V	3A	1-3/8" Threaded*	Optional	5613-1	AS5612S-1	AS5612E-1	—
Tsunami Mk2 Bilge Replacement Motor Cartridges								
T500	12V							5620-6
T800	12V							5622-6
T1200	12V							5624-6

Wire Length for all models 29" (735mm). *Must be used with appropriate Tsunami outlet.

Service Kits:

- AK5605-7 for T500 and T800
- AK5612-7 for T1200
- Service kits for Barb versions not available



5606



5608



5612

12 Volt Specifications

Model	Automotive Fuse Required (amps)	NRV Fitted	ABYC Specifications 13.6-volts DC (GPH=Gallons Per Hour)			ISO Specifications 12.0-volts DC (LPH=Liters Per Hour)			
			0 ft. Head GPH/amps	3.3 ft. Head GPH/amps	6.7 ft. Head GPH/amps	0m Head LPH/amps	1m Head LPH/amps	2m Head LPH/amps	Max Head (ft@13.6V/m@12V)
T500	3	N	536/1.7	334/2.2	200/2.1	1818/1.5	1156/1.5	0	7.6/1.8
	3	Y	510/1.8	311/2.2	186/2.1	1692/1.5	1116/1.5	0	7.6/1.8
T800	4	N	796/3.1	503/3.6	356/3.4	2682/2.6	2246/2.6	1554/2.6	14.2/3.5
	4	Y	747/3.2	482/3.5	341/3.3	2544/2.6	2076/2.6	1440/2.6	14.2/3.5
T1200	5	N	1155/3.9	789/4.5	565/4.3	4002/3.3	3007/3.4	1764/3.2	11.8/2.9
	5	Y	903/4.0	659/4.4	464/4.2	3124/3.4	2356/3.3	1364/3.0	11.8/2.9

24 Volt Specifications

Model	Automotive Fuse Required (amps)	NRV Fitted	ABYC Specifications 27.2-volts DC (GPH=Gallons Per Hour)			ISO Specifications 24.0-volts DC (LPH=Liters Per Hour)			
			0 ft. Head GPH/amps	3.3 ft. Head GPH/amps	6.7 ft. Head GPH/amps	0m Head LPH/amps	1m Head LPH/amps	2m Head LPH/amps	Max Head (ft@27.2V/m@24V)
T800	2	N	802/1.5	472/1.5	340/1.4	3036/1.5	2262/1.6	1977/1.5	14.8/3.5
	2	Y	737/1.6	454/1.5	322/1.4	2532/1.3	2046/1.3	1464/1.2	14.8/3.5
T1200	2	N	1106/1.8	698/1.9	474/1.8	3816/1.5	2817/1.5	1479/1.4	11.1/2.7
	2	Y	859/1.9	602/1.8	384/1.7	2946/1.6	2223/1.5	1203/1.4	11.1/2.7

Mounting Pattern Compatibility

Tsunami Mk1 500

Tsunami Mk1 800 / 1200

Johnson L Series

