

Distribution Stud

The Heavy-Duty Distribution Stud allows terminating of heavy-duty cables for one or more connections. Contour Lock housing has removable side plates which allows for connections from all sides.

OEM # 702B



Dual Distribution Stud

Designed specifically for transom areas for connecting battery cables from outboards. It also has many other applications where heavy-duty positive and negative connections need to be terminated.

OEM # 702-2S/B




4-way Distribution Stud

The 704-4S was designed for multiple heavy-duty connections which need to be isolated from each other. This model completes the range of heavy-duty connectors and meets ABYC standards for exposed terminals.


OEM # 704-4S/B

The patented Contour Locking System is an innovative feature that allows for multiple battery management components to be connected to each other providing a clean finished installation. These locking tabs can be found on battery switches, heavy-duty buss bars, fuse holders, distribution studs and breaker modules.

Description	Stud Size	OEM#	LxWxH in	LxWxH mm
Distribution Stud	10 mm (3/8")	702B	2.75" x 2.75" x 2"	69 x 69 x 50 mm
Dual Distribution Stud	2x 10 mm (3/8")	702-2S/B	2.75" x 2.75" x 2"	69 x 69 x 50 mm
	1x 8 mm (5/16") 1x 10 mm (3/8")	702-8-10-B	2.75" x 2.75" x 2"	69 x 69 x 50 mm
Dual Distribution Stud with Link Plate	2x 10 mm (3/8")	702-2SB/L	2.75" x 2.75" x 2"	69 x 69 x 50 mm
4-way Distribution Stud	4x 10 mm (3/8")	704-4S/B	5.3" x 2.75" x 2"	138 x 69 x 50 mm



19 mm Suits 701



25 mm Suits 720



Terminal Links

The 708 links are designed for space saving interconnections of terminals when battery distribution modules are linked together. Four standard solid links are available for interconnection of the 701 battery switch with other Battery Distribution products and two larger links which are intended for the heavy-duty battery switch.

Part #	Distance between centers	Hole diameter
708-42.5	1.7" (43 mm)	3/8" (10 mm)
708-54.5	2.2" (55 mm)	3/8" (10 mm)
708-64.5	2.5" (65 mm)	3/8" (10 mm)
708-68.5	2.7" (69 mm)	3/8" (10 mm)
708-62.0	2.45" (62 mm)	1/2" (12 mm)



Secondary Bus

Fitted to Distribution Stud 702 allows for small wire connections without cluttering main stud. Terminal screws 1/8" (4 mm).

Part # 702SB

